



ITEM SPEC SHEET

Tolerances: +/- 5% of Gauge and Size

1. Item Type

Commercial / Industrial	<input type="checkbox"/> White	<input type="checkbox"/> Brown
Retail	<input type="checkbox"/> Club Box	<input type="checkbox"/> Pouched
	<input type="checkbox"/> Chipboard (Cereal)	<input type="checkbox"/> Per Master Box
	<input type="checkbox"/> Per Master Box	<input type="checkbox"/> Per Master Box

Company:		Date:
Address:		
City:	St:	Zip:
Cell:		
Email:		Contact:
Rep:		Order Deadline: / /

2. Bag Specs

Gallon Size Comparison

Highlighted are most popular

Width:	4 GAL	7-10 GAL	12-13-16 GAL	33 GAL	40-42-45 GAL	45 GAL	56 GAL	50-55 GAL	55-60 GAL
Gusset:	13x4x17 17x18	10x8x24	15x9x31	20x13x39	23x10x48	18x16x45	23x20x46	22x14x58	22x16x58
Length:		15x9x23	24x27	23x10x39	32x50	23x17x46	26x24x48	32x58	38x55
Gauge:		18x24	24x31	33x39	33x46	40x46	43x47	36x60	38x58
Per Case:		24x24	24x32	33x40	33x47	40x47	43x48		38x59
		24x24	24x33		33x48	40x48			38x60

Bag Drawing:

3. Material Sorted by Least Expensive

Hi-Density	Low-Density (LDPE)																																																																																																																	
<input type="checkbox"/> High Density HDPE is the ideal material for NON-SHARP objects <table border="1"> <thead> <tr> <th colspan="2">Hi-Density</th> </tr> <tr> <th>GAUGE</th> <th>MAX LOAD</th> </tr> </thead> <tbody> <tr><td>6</td><td>16</td></tr> <tr><td>8</td><td>20</td></tr> <tr><td>10</td><td>30</td></tr> <tr><td>13</td><td>55</td></tr> <tr><td>14</td><td>55</td></tr> <tr><td>16</td><td>70</td></tr> <tr><td>17</td><td>75</td></tr> <tr><td>19</td><td>80</td></tr> <tr><td>22</td><td>85</td></tr> </tbody> </table>	Hi-Density		GAUGE	MAX LOAD	6	16	8	20	10	30	13	55	14	55	16	70	17	75	19	80	22	85	<input type="checkbox"/> Repro Plastics Cloudier than conventional industrial film; not recommended for food contact <input type="checkbox"/> Post Consumer Repro 80% recycled material and a minimum of 10% post consumer up to 40% <table border="1"> <thead> <tr> <th colspan="2">Repro & Post</th> </tr> <tr> <th>GAUGE</th> <th>MAX LOAD</th> </tr> </thead> <tbody> <tr><td>0.8</td><td>32</td></tr> <tr><td>1</td><td>40</td></tr> <tr><td>1.2</td><td>48</td></tr> <tr><td>1.3</td><td>52</td></tr> <tr><td>1.5</td><td>60</td></tr> <tr><td>1.6</td><td>64</td></tr> <tr><td>1.7</td><td>68</td></tr> <tr><td>1.9</td><td>76</td></tr> <tr><td>2</td><td>80</td></tr> </tbody> </table>	Repro & Post		GAUGE	MAX LOAD	0.8	32	1	40	1.2	48	1.3	52	1.5	60	1.6	64	1.7	68	1.9	76	2	80	<input type="checkbox"/> Metalocene / Aluene Blend LDPE recycled blend of super strength prime resins, enables a 10% thinner gauge, yet stronger <table border="1"> <thead> <tr> <th colspan="2">Aluene</th> </tr> <tr> <th>GAUGE</th> <th>MAX LOAD</th> </tr> </thead> <tbody> <tr><td>0.8</td><td>36</td></tr> <tr><td>1</td><td>45</td></tr> <tr><td>1.2</td><td>54</td></tr> <tr><td>1.3</td><td>59</td></tr> <tr><td>1.5</td><td>68</td></tr> <tr><td>1.6</td><td>72</td></tr> <tr><td>1.7</td><td>77</td></tr> <tr><td>1.9</td><td>86</td></tr> <tr><td>2</td><td>90</td></tr> </tbody> </table>	Aluene		GAUGE	MAX LOAD	0.8	36	1	45	1.2	54	1.3	59	1.5	68	1.6	72	1.7	77	1.9	86	2	90	<input type="checkbox"/> Butene LLDPE blend-up to 20% stronger than LDPE <input type="checkbox"/> Butene High Clarity LDPE typically used for food applications <table border="1"> <thead> <tr> <th colspan="2">Butene</th> </tr> <tr> <th>GAUGE</th> <th>MAX LOAD</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>22</td></tr> <tr><td>0.6</td><td>33</td></tr> <tr><td>0.7</td><td>39</td></tr> <tr><td>0.8</td><td>44</td></tr> <tr><td>0.9</td><td>50</td></tr> <tr><td>1</td><td>55</td></tr> <tr><td>1.3</td><td>72</td></tr> <tr><td>1.5</td><td>83</td></tr> <tr><td>2</td><td>110</td></tr> </tbody> </table>	Butene		GAUGE	MAX LOAD	0.4	22	0.6	33	0.7	39	0.8	44	0.9	50	1	55	1.3	72	1.5	83	2	110	<input type="checkbox"/> Super Hexene Our strongest and best material strength / impact resistance up to 50% stronger than LDPE <table border="1"> <thead> <tr> <th colspan="2">Super Hexene</th> </tr> <tr> <th>GAUGE</th> <th>MAX LOAD</th> </tr> </thead> <tbody> <tr><td>0.4</td><td>30</td></tr> <tr><td>0.6</td><td>45</td></tr> <tr><td>0.7</td><td>53</td></tr> <tr><td>0.8</td><td>60</td></tr> <tr><td>0.9</td><td>68</td></tr> <tr><td>1</td><td>75</td></tr> <tr><td>1.3</td><td>98</td></tr> <tr><td>1.5</td><td>113</td></tr> <tr><td>2</td><td>150</td></tr> </tbody> </table>	Super Hexene		GAUGE	MAX LOAD	0.4	30	0.6	45	0.7	53	0.8	60	0.9	68	1	75	1.3	98	1.5	113	2	150
Hi-Density																																																																																																																		
GAUGE	MAX LOAD																																																																																																																	
6	16																																																																																																																	
8	20																																																																																																																	
10	30																																																																																																																	
13	55																																																																																																																	
14	55																																																																																																																	
16	70																																																																																																																	
17	75																																																																																																																	
19	80																																																																																																																	
22	85																																																																																																																	
Repro & Post																																																																																																																		
GAUGE	MAX LOAD																																																																																																																	
0.8	32																																																																																																																	
1	40																																																																																																																	
1.2	48																																																																																																																	
1.3	52																																																																																																																	
1.5	60																																																																																																																	
1.6	64																																																																																																																	
1.7	68																																																																																																																	
1.9	76																																																																																																																	
2	80																																																																																																																	
Aluene																																																																																																																		
GAUGE	MAX LOAD																																																																																																																	
0.8	36																																																																																																																	
1	45																																																																																																																	
1.2	54																																																																																																																	
1.3	59																																																																																																																	
1.5	68																																																																																																																	
1.6	72																																																																																																																	
1.7	77																																																																																																																	
1.9	86																																																																																																																	
2	90																																																																																																																	
Butene																																																																																																																		
GAUGE	MAX LOAD																																																																																																																	
0.4	22																																																																																																																	
0.6	33																																																																																																																	
0.7	39																																																																																																																	
0.8	44																																																																																																																	
0.9	50																																																																																																																	
1	55																																																																																																																	
1.3	72																																																																																																																	
1.5	83																																																																																																																	
2	110																																																																																																																	
Super Hexene																																																																																																																		
GAUGE	MAX LOAD																																																																																																																	
0.4	30																																																																																																																	
0.6	45																																																																																																																	
0.7	53																																																																																																																	
0.8	60																																																																																																																	
0.9	68																																																																																																																	
1	75																																																																																																																	
1.3	98																																																																																																																	
1.5	113																																																																																																																	
2	150																																																																																																																	

4. Film Color

<input type="checkbox"/> Tint (see-through)	<input type="checkbox"/> Opaque (Above 1 mil - Conceals Contents)	<input type="checkbox"/> Black	<input type="checkbox"/> Blue	<input type="checkbox"/> Yellow	<input type="checkbox"/> Red	<input type="checkbox"/> White	<input type="checkbox"/> Clear	<input type="checkbox"/> Other _____
---	---	--------------------------------	-------------------------------	---------------------------------	------------------------------	--------------------------------	--------------------------------	--------------------------------------

5. Seal

<input type="checkbox"/> Star Seal The strongest most common seal 	<input type="checkbox"/> Flat Seal Generally used for 3 mil and thicker 	<input type="checkbox"/> Gusset Seal Classic janitorial favorite 	<input type="checkbox"/> Poly Tubing To be tied or sealed by user 	<input type="checkbox"/> M-Fold Furniture / Pallet Cover 	Sheeting <input type="checkbox"/> Single Wound Sheeting <input type="checkbox"/> Center Fold Sheeting <input type="checkbox"/> Center Fold Gusseted <input type="checkbox"/> Center Slit Gusseted
---	---	--	---	--	--

6. Pack

7. Closures (Optional)

<input type="checkbox"/> Individually Folded	<input type="checkbox"/> Bulk Fold, Gang / Flat Pack	<input type="checkbox"/> 3" Cored Rolls	<input type="checkbox"/> 1.5" Cored Rolls	<input type="checkbox"/> Perforated Coreless Rolls	<input type="checkbox"/> Bags per Interleaved Coreless Rolls	<input type="checkbox"/> Hand Tie	<input type="checkbox"/> Twist Tie	<input type="checkbox"/> Flaps Coreless Rolls	<input type="checkbox"/> Drawstring on Coreless Rolls

8. Add-On's (Check With Factory)

<input type="checkbox"/> Print Ink Color Random Printing One Color, One Side <input type="checkbox"/> Other _____	<input type="checkbox"/> Anti-Stat <input type="checkbox"/> Twist Ties <input type="checkbox"/> Embossing	<input type="checkbox"/> UVI <input type="checkbox"/> Fluttered Punch (Half Moon) <input type="checkbox"/> Knock-Out Punch <input type="checkbox"/> Pinhole Punch <input type="checkbox"/> X Punch 	Vents / Width of Bag: _____ i.e. 2" from one side of bag or 2" from each side Vents / Length of Bag: _____ i.e. every 6" Fluttered or Knock-Out Punch Size: <input type="checkbox"/> 1/4 Inch <input type="checkbox"/> 3/8 Inch
---	---	--	---

9. Label Information Optional

(20 Character Limit including Spaces per Line)

1:
2:
3:
4:
5:

10. Market / Competitive Information Optional

Sample Provided: <input type="checkbox"/> Yes <input type="checkbox"/> No
Manufacturer:
Item:
Current Price:
Case per Order:
Frequency of Order:
Notes: